OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

N32U

N32U210000000M0
METER TEMP AC/DC INPUT 1R RS485



- Programmable digital meter of temperature, resistance and standard signals
- Universal Measuring input
- Two-line LCD display
- RS-485 digital output as standard

PRODUCT DESCRIPTION

The new N32U distinguishes modern and easy to read LCD display, a universal measuring input, and an RS-485 digital output as standard on all products.

The universal input can be used for measuring temperature, standard signals and resistance. Two-line LCD display means it comes with built in backlighting and high contrast. There is a possibility of displaying the measured value and time simultaneously or an uncalculated quantity or unit (programme unit of measured quantity). With up to 4 alarm outputs with signalling on led diodes, working in seven different diodes.
Another option is a conversion of any measured value into an analog signal 0/4...20 mA or 0...10V.

Programming can be done via keyboard or through RS-485 interface by means of the free eCon software.

TECHNICAL DATA

Display	Yes
IP class	IP65
Mounting	Panel mount
Number of rows	2
Outputs	4 Relays, RS-485
Supply voltage	20-40Vac/20-60Vdc

Weight	0.36 kg