

## JUNG HYGHSPIN SERIES PUMP

Hygienic twin scrow pump

JPS HYGHSPIN 125

- Flow 30l/h to 300 m³/h
- Pressure up to 35 bar
- Viscosity up to 1,000,000 cSt
- Temperature -10°C to +130°C (180°C)
- Max. particle size 45mm



### PRODUCT DESCRIPTION

The HYGHSPIN is the Standard model from the worldwide tried and tested HYGHSPIN pump series made of high-quality stainless steel. Whether aqueous, highly viscous, lumpy, fibrous or gas loaded - the HYGHSPIN is suitable for products of virtually any consistency and is characterised by its high efficiency. The particularly service-friendly twin screw pump impresses with a very high suction power and gently transports all flow capable products in volumes of up to 300 m³/h. An additional pump for CIP cleaning is not necessary: A considerable time and cost saving due to reduced investment and maintenance costs is thereby guaranteed.

### TECHNICAL DATA

Connection type	Different sizes and connector standards by arrangement
Differential pressure	35 bar
Flow max	300 m³/h
Material of elastomers	EPDM, FPM, HNBR (Nitrile rubber), FFPM
Material of wetted parts	Stainless steel 316/316L (1.4401/1.4404), Stainless steel 1.4462, 1.4404, Stainless Steel 1.4539
Maximum diameter of solid material	45 mm
Pump orientation	Horizontal, vertical or lateral
Temperature operational max	180 °C
Temperature operational min	-10 °C
Viscosity	0.5 - 1,000,000 mPas