

SAMOA 1/4" PNEUMATIC DIAPHRAGM PUMP

Non-Metallic

DC20P-PST-PTT-BAS
DC20, AODD Pump, 1/4", Polypropylene, Teflon, 20 LPM

- Pump Size 1/4"
- Connection Types - BSP, Center Ports
- Max. Flow Rate 20 LPM
- Operating Pressure 1.5 - 7 bar

PRODUCT DESCRIPTION

TECHNICAL DATA

Approvals	CE, UKCA
Country of origin	Spain
Diaphragm Type	Overmoulded
Fluid Displacement Per Cycle	0.06 litres
Fluid Port Connection Type	BSP Center Ports
Material Air Section (Central Body & Air cover)	Polypropylene
Material Of Diaphragm	PTFE
Material of valve ball	PTFE
Material of valve seats	Polypropylene
Material of wetted parts	Polypropylene
Max suction lift - Dry	2 m
Max suction lift - Wet	7 m
Max. Flow Rate	20 LPM
Max. Size Of Suspended Solids	2 mm
Net Dimensions	142mm x 142mm x 173mm
Net Weight	1.2 kg
Operating Pressure	1.5 - 7 bar
Pump size	1/4"
Pump type	Non-Metallic
Tariff code	8413508090

Type

Standard Pump