

SAMOA 3/8" PNEUMATIC DIAPHRAGM PUMP

Non-Metallic

UP03B-BBS-PTA
UP03, AODD Pump, 3/8", Polypropylene, Teflon,
Santoprene, 31 LPM, ATEX

- Pump Size 3/8"
- Connection Types - BSP/NPT, Side Ports
- Max. Flow Rate 31 LPM
- Operating Pressure 1.5 - 7 bar

PRODUCT DESCRIPTION

TECHNICAL DATA

Approvals	CE ATEX, UKCA, EAC
Country of origin	Spain
Diaphragm Type	Convolutud
Fluid Displacement Per Cycle	0.08 litres
Fluid Port Connection Type	BSP Side Ports
Material Air Section (Central Body & Air cover)	Conductive Polypropylene
Material Of Diaphragm	Santoprene
Material of valve ball	PTFE
Material of valve seats	Polypropylene
Material of wetted parts	Conductive Polypropylene
Max suction lift - Dry	3 m
Max suction lift - Wet	7 m
Max. Flow Rate	31 LPM
Max. Size Of Suspended Solids	1.6 mm
Net Weight	2 kg
Operating Pressure	1.5 - 7 bar
Pump size	3/8"
Pump type	Non-Metallic
Tariff code	8413508090
Type	Key Model Pump

