

## SAMOA 3/8" PNEUMATIC DIAPHRAGM PUMP

Non-Metallic

UP03B-NDS-CCZ  
UP03, AODD Pump, 3/8", Polypropylene, Acetal,  
Teflon, 31 LPM, ATEX

- Pump Size 3/8"
- Connection Types - BSP/NPT, Side Ports
- Max. Flow Rate 31 LPM
- Operating Pressure 1.5 - 7 bar

### PRODUCT DESCRIPTION

### TECHNICAL DATA

Approvals	CE ATEX, UKCA, EAC
Country of origin	Spain
Diaphragm Type	2-Piece
Fluid Displacement Per Cycle	0.08 litres
Fluid Port Connection Type	NPT Side Ports
Material Air Section (Central Body & Air cover)	Conductive Polypropylene
Material Of Diaphragm	PTFE
Material of valve ball	Acetal
Material of valve seats	Acetal
Material of wetted parts	Conductive Acetal
Max suction lift - Dry	3 m
Max suction lift - Wet	7 m
Max. Flow Rate	31 LPM
Max. Size Of Suspended Solids	1.6 mm
Net Dimensions	202mm x 151mm x 237mm
Net Weight	2.1 kg
Operating Pressure	1.5 - 7 bar
Pump size	3/8"
Pump type	Non-Metallic
Tariff code	8413508090

Type	Key Model Pump
------	----------------