

OEM Automatic Ltd

Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk



SAMOA 3/8\" PNEUMATIC DIAPHRAGM PUMP

Non-Metallic

UP03B-NPS-PTA UP03, AODD Pump, 3/8", Polypropylene, Teflon, Santoprene, 31 LPM

- Pump Size 3/8"
- Connection Types BSP/NPT, Side Ports
- Max. Flow Rate 31 LPM
- Operating Pressure 1.5 7 bar

PRODUCT DESCRIPTION

TECHNICAL DATA

Approvals	CE, UKCA
Country of origin	Spain
Diaphragm Type	Convoluted
Fluid Displacement Per Cycle	0.08 litres
Fluid Port Connection Type	NPT Side Ports
Material Air Section (Central Body & Air cover)	Conductive Polypropylene
Material Of Diaphragm	Santoprene
Material of valve ball	PTFE
Material of valve seats	Polypropylene
Material of wetted parts	Polypropylene
Max suction lift - Dry	3 m
Max suction lift - Wet	7 m
Max. Flow Rate	31 LPM
Max. Size Of Suspended Solids	1.6 mm
Net Dimensions	202mm x 151mm x 237mm
Net Weight	1.8 kg
Operating Pressure	1.5 - 7 bar
Pump size	3/8"
Pump type	Non-Metallic
Tariff code	8413508090