

OEM Automatic Ltd

Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk



SAMOA 3/8\" PNEUMATIC DIAPHRAGM PUMP

Non-Metallic

UP03B-BPS-PTZ UP03, AODD Pump, 3/8", Polypropylene, Teflon, 31 LPM

- Pump Size 3/8"
- Connection Types BSP/NPT, Side Ports
- Max. Flow Rate 31 LPM
- Operating Pressure 1.5 7 bar

PRODUCT DESCRIPTION

TECHNICAL DATA

Approvals	CE, UKCA
Country of origin	Spain
Diaphragm Type	2-Piece
Fluid Displacement Per Cycle	0.08 litres
Fluid Port Connection Type	BSP Side Ports
Material Air Section (Central Body & Air cover)	Conductive Polypropylene
Material Of Diaphragm	PTFE
Material of valve ball	PTFE
Material of valve seats	Polypropylene
Material of wetted parts	Polypropylene
Max suction lift - Dry	3 m
Max suction lift - Wet	7 m
Max. Flow Rate	31 LPM
Max. Size Of Suspended Solids	1.6 mm
Net Dimensions	202mm x 151mm x 237mm
Net Weight	1.8 kg
Operating Pressure	1.5 - 7 bar
Pump size	3/8"
Pump type	Non-Metallic
Tariff code	8413508090