

SAMOA 1/2" PNEUMATIC DIAPHRAGM PUMP

Metallic / Non-Metallic

UP05A-NAC-SSZ
UP05, AODD Pump, 1/2", Aluminium, 316 Stainless
Steel, Teflon, 54 LPM, ATEX

- Pump Size 1/2"
- Connection Types - BSP/NPT, Side/Center/Multiple/Dual Ports
- Max. Flow Rate 51-54 LPM
- Operating Pressure 1.5 - 7 / 1.5 - 8 bar

PRODUCT DESCRIPTION

TECHNICAL DATA

Approvals	CE ATEX, UKCA, EAC
Country of origin	Spain
Diaphragm Type	2-Piece
Fluid Displacement Per Cycle	0.15 litres
Fluid Port Connection Type	NPT Side Ports
Material Air Section (Central Body & Air cover)	Aluminium
Material Of Diaphragm	PTFE
Material of valve ball	Stainless steel 316
Material of valve seats	Stainless steel 316
Material of wetted parts	Aluminium
Max suction lift - Dry	5 m
Max suction lift - Wet	8 m
Max. Flow Rate	54 LPM
Max. Size Of Suspended Solids	2.5 mm
Net Dimensions	216mm x 162mm x 299mm
Net Weight	3.9 kg
Operating Pressure	1.5 - 8 bar
Pump size	1/2"
Pump type	Metallic

Tariff code

8413508090

Type

Special Pump