OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

SAMOA 1/2\" PNEUMATIC DIAPHRAGM PUMP

Metallic / Non-Metallic

UP05A-BAC-SVV
UP05, AODD Pump, 1/2", Aluminium, 316 Stainless Steel, Viton, 54 LPM, ATEX



- Pump Size 1/2"
- Connection Types - BSP/NPT, Side/Center/Multiple/Dual Ports
- Max. Flow Rate 51-54 LPM
- Operating Pressure 1.5 - 7 / 1.5 - 8 bar

PRODUCT DESCRIPTION

TECHNICAL DATA

Approvals	CE ATEX, UKCA, EAC
Country of origin	Spain
Diaphragm Type	Convoluted
Fluid Displacement Per Cycle	0.15 litres
Fluid Port Connection Type	BSP Center Ports
Material Air Section (Central Body & Air cover)	Aluminium
Material Of Diaphragm	Viton
Material of valve ball	Viton
Material of valve seats	Stainless steel 316
Material of wetted parts	Aluminium
Max suction lift - Dry	5 m
Max suction lift - Wet	8 m
Max. Flow Rate	54 LPM
Max. Size Of Suspended Solids	2.5 mm
Net Dimensions	216mm x 162mm x 299mm
Net Weight	3.9 kg

Operating Pressure	1.5 - 8 bar
Pump size	1/2"
Pump type	Metallic
Tariff code	8413508090
Type	Special Pump