

SAMOA 1/2" PNEUMATIC DIAPHRAGM PUMP

Metallic / Non-Metallic

UP05A-BSS-SMA
UP05, AODD Pump, 1/2", Aluminium, 316 Stainless
Steel, Santoprene, 54 LPM, ATEX

- Pump Size 1/2"
- Connection Types - BSP/NPT, Side/Center/Multiple/Dual Ports
- Max. Flow Rate 51-54 LPM
- Operating Pressure 1.5 - 7 / 1.5 - 8 bar

PRODUCT DESCRIPTION

TECHNICAL DATA

Approvals	CE ATEX, UKCA, EAC
Country of origin	Spain
Diaphragm Type	Convuluted
Fluid Displacement Per Cycle	0.15 litres
Fluid Port Connection Type	BSP Center Ports
Material Air Section (Central Body & Air cover)	Aluminium
Material Of Diaphragm	Santoprene
Material of valve ball	Santoprene
Material of valve seats	Stainless steel 316
Material of wetted parts	Stainless steel 316
Max suction lift - Dry	5 m
Max suction lift - Wet	8 m
Max. Flow Rate	54 LPM
Max. Size Of Suspended Solids	2.5 mm
Net Dimensions	193mm x 161mm x 295mm
Net Weight	6.5 kg
Operating Pressure	1.5 - 8 bar
Pump size	1/2"
Pump type	Metallic

Tariff code	8413508090
Type	Key Model Pump