OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

SAMOA 1/2\" PNEUMATIC DIAPHRAGM PUMP

Metallic / Non-Metallic

UP05A-NSS-STZ
UP05, AODD Pump, 1/2", Aluminium, 316 Stainless Steel, Teflon, 54 LPM, ATEX



- Pump Size 1/2"
- Connection Types - BSP/NPT, Side/Center/Multiple/Dual Ports
- Max. Flow Rate 51-54 LPM
- Operating Pressure 1.5 - 7 / 1.5 - 8 bar

PRODUCT DESCRIPTION

TECHNICAL DATA

Approvals	CE ATEX, UKCA, EAC
Country of origin	Spain
Diaphragm Type	2-Piece
Fluid Displacement Per Cycle	0.15 litres
Fluid Port Connection Type	NPT Center Ports
Material Air Section (Central Body & Air cover)	Aluminium
Material Of Diaphragm	PTFE
Material of valve ball	PTFE
Material of valve seats	Stainless steel 316
Material of wetted parts	Stainless steel 316
Max suction lift - Dry	5 m
Max suction lift - Wet	8 m
Max. Flow Rate	54 LPM
Max. Size Of Suspended Solids	2.5 mm
Net Dimensions	193mm x 161mm x 295mm
Net Weight	6.5 kg

Operating Pressure	1.5 - 8 bar
Pump size	1/2"
Pump type	Metallic
Tariff code	8413508090
Type	Key Model Pump