

SAMOA 1/2" PNEUMATIC DIAPHRAGM PUMP

Metallic / Non-Metallic

UP05B-BDS-SSZ
UP05, AODD Pump, 1/2", Polypropylene, Acetal, 316
Stainless Steel, Teflon, 51 LPM, ATEX

- Pump Size 1/2"
- Connection Types - BSP/NPT, Side/Center/Multiple/Dual Ports
- Max. Flow Rate 51-54 LPM
- Operating Pressure 1.5 - 7 / 1.5 - 8 bar

PRODUCT DESCRIPTION

TECHNICAL DATA

Approvals	CE ATEX, UKCA, EAC
Country of origin	Spain
Diaphragm Type	2-Piece
Fluid Displacement Per Cycle	0.15 litres
Fluid Port Connection Type	BSP Multiple Ports
Material Air Section (Central Body & Air cover)	Conductive Polypropylene
Material Of Diaphragm	PTFE
Material of valve ball	Stainless steel 316
Material of valve seats	Stainless steel 316
Material of wetted parts	Conductive Acetal
Max suction lift - Dry	5 m
Max suction lift - Wet	8 m
Max. Flow Rate	51 LPM
Max. Size Of Suspended Solids	2.5 mm
Net Dimensions	250mm x 161mm x 278mm
Net Weight	3.3 kg
Operating Pressure	1.5 - 7 bar
Pump size	1/2"
Pump type	Non-Metallic

Tariff code

8413508090

Type

Special Pump