

SAMOA 1" PNEUMATIC DIAPHRAGM PUMP

Metallic / Non-Metallic

UP10A-BFC-MMA
UP10, AODD Pump, 1", Aluminium, Ductile Iron,
Santoprene, 200 LPM, ATEX

- Pump Size 1"
- Connection Types - BSP/NPT, Side/Center/Multiple Ports, ANSI/DIN Center/Side Flange
- Max. Flow Rate 130-200 LPM
- Operating Pressure 1.5 - 7 / 1.5 - 8 bar

PRODUCT DESCRIPTION

TECHNICAL DATA

Approvals	CE ATEX, UKCA, EAC
Country of origin	Spain
Diaphragm Type	Convoluted
Fluid Displacement Per Cycle	0.85 litres
Fluid Port Connection Type	BSP Multiple Ports
Material Air Section (Central Body & Air cover)	Aluminium
Material Of Diaphragm	Santoprene
Material of valve ball	Santoprene
Material of valve seats	Santoprene
Material of wetted parts	Ductile iron
Max suction lift - Dry	5 m
Max suction lift - Wet	8 m
Max. Flow Rate	200 LPM
Max. Size Of Suspended Solids	6.4 mm
Net Dimensions	348mm x 237mm x 317mm
Net Weight	17.5 kg
Operating Pressure	1.5 - 8 bar
Pump size	1"
Pump type	Metallic

Tariff code

8413508090

Type

Key Model Pump