

SAMOA 1" PNEUMATIC DIAPHRAGM PUMP

Metallic / Non-Metallic

UP10B-NBS-PMA
UP10, AODD Pump, 1", Polypropylene, Santoprene,
200 LPM, ATEX

- Pump Size 1"
- Connection Types - BSP/NPT, Side/Center/Multiple Ports, ANSI/DIN Center/Side Flange
- Max. Flow Rate 130-200 LPM
- Operating Pressure 1.5 - 7 / 1.5 - 8 bar

PRODUCT DESCRIPTION

TECHNICAL DATA

Approvals	UKCA, CE
Country of origin	Spain
Diaphragm Type	Convoluted
Fluid Displacement Per Cycle	0.85 litres
Fluid Port Connection Type	NPT Center Ports
Material Air Section (Central Body & Air cover)	Conductive Polypropylene
Material Of Diaphragm	Santoprene
Material of valve ball	Santoprene
Material of valve seats	Polypropylene
Material of wetted parts	Conductive Polypropylene
Max suction lift - Dry	5 m
Max suction lift - Wet	8 m
Max. Flow Rate	200 LPM
Max. Size Of Suspended Solids	6.4 mm
Net Dimensions	399mm x 243mm x 386mm
Net Weight	11.6 kg
Operating Pressure	1.5 - 7 bar
Pump size	1"
Pump type	Non-Metallic

Tariff code

8413508090

Type

Key Model Pump