

SAMOA 1" PNEUMATIC DIAPHRAGM PUMP

Metallic / Non-Metallic

UP10B-NPS-PNG

UP10, AODD Pump, 1", Polypropylene, NBR, 200 LPM

- Pump Size 1"
- Connection Types - BSP/NPT, Side/Center/Multiple Ports, ANSI/DIN Center/Side Flange
- Max. Flow Rate 130-200 LPM
- Operating Pressure 1.5 - 7 / 1.5 - 8 bar

PRODUCT DESCRIPTION

TECHNICAL DATA

Approvals	UKCA, CE
Country of origin	Spain
Diaphragm Type	Convolute
Fluid Displacement Per Cycle	0.85 litres
Fluid Port Connection Type	NPT Center Ports
Material Air Section (Central Body & Air cover)	Conductive Polypropylene
Material Of Diaphragm	Buna-N
Material of valve ball	Buna-N
Material of valve seats	Polypropylene
Material of wetted parts	Polypropylene
Max suction lift - Dry	5 m
Max suction lift - Wet	8 m
Max. Flow Rate	200 LPM
Max. Size Of Suspended Solids	6.4 mm
Net Dimensions	399mm x 243mm x 386mm
Net Weight	10.2 kg
Operating Pressure	1.5 - 7 bar
Pump size	1"
Pump type	Non-Metallic

Tariff code	8413508090
Type	Standard Pump