

SAMOA 1" PNEUMATIC DIAPHRAGM PUMP

Metallic / Non-Metallic

UP10B-TPS-PTZ
UP10, AODD Pump, 1", Polypropylene, Teflon, 200 LPM

- Pump Size 1"
- Connection Types - BSP/NPT, Side/Center/Multiple Ports, ANSI/DIN Center/Side Flange
- Max. Flow Rate 130-200 LPM
- Operating Pressure 1.5 - 7 / 1.5 - 8 bar

PRODUCT DESCRIPTION

TECHNICAL DATA

Approvals	UKCA, CE
Country of origin	Spain
Diaphragm Type	2-Piece
Fluid Displacement Per Cycle	0.85 litres
Fluid Port Connection Type	NPT Side Ports
Material Air Section (Central Body & Air cover)	Conductive Polypropylene
Material Of Diaphragm	PTFE
Material of valve ball	PTFE
Material of valve seats	Polypropylene
Material of wetted parts	Polypropylene
Max suction lift - Dry	5 m
Max suction lift - Wet	8 m
Max. Flow Rate	200 LPM
Max. Size Of Suspended Solids	6.4 mm
Net Dimensions	399mm x 243mm x 386mm
Net Weight	10.2 kg
Operating Pressure	1.5 - 7 bar
Pump size	1"
Pump type	Non-Metallic

Tariff code

8413508090

Type

Key Model Pump