

SAMOA 1.5" PNEUMATIC DIAPHRAGM PUMP

Metallic

UP15A-BAC-AVV
UP15, AODD Pump, 1.5", Aluminium, Viton, 470 LPM,
ATEX

- Pump Size 1.5"
- Connection Types - BSP/NPT, Multiple Ports
- Max. Flow Rate 470 LPM
- Operating Pressure 1.5 - 8 bar

PRODUCT DESCRIPTION

TECHNICAL DATA

Approvals	CE ATEX, UKCA, EAC
Country of origin	Spain
Diaphragm Type	Convolute
Fluid Displacement Per Cycle	2.5 litres
Fluid Port Connection Type	BSP Multiple Ports
Material Air Section (Central Body & Air cover)	Aluminium
Material Of Diaphragm	Viton
Material of valve ball	Viton
Material of valve seats	Aluminium
Material of wetted parts	Aluminium
Max suction lift - Dry	5.9 m
Max suction lift - Wet	9 m
Max. Flow Rate	470 LPM
Max. Size Of Suspended Solids	6.4 mm
Net Dimensions	455.5mm x 326mm x 517.5mm
Net Weight	22 kg
Operating Pressure	1.5 - 8 bar
Pump size	1.5"
Pump type	Metallic
Tariff code	8413508090

Type	Key Model Pump
------	----------------