

SAMOA 1.5" PNEUMATIC DIAPHRAGM PUMP

Metallic

UP15A-BAC-STZ
UP15, AODD Pump, 1.5", Aluminium, 316 Stainless
Steel, Teflon, 470 LPM, ATEX

- Pump Size 1.5"
- Connection Types - BSP/NPT, Multiple Ports
- Max. Flow Rate 470 LPM
- Operating Pressure 1.5 - 8 bar

PRODUCT DESCRIPTION

TECHNICAL DATA

Approvals	CE ATEX, UKCA, EAC
Country of origin	Spain
Diaphragm Type	2-Piece
Fluid Displacement Per Cycle	2.5 litres
Fluid Port Connection Type	BSP Multiple Ports
Material Air Section (Central Body & Air cover)	Aluminium
Material Of Diaphragm	PTFE
Material of valve ball	PTFE
Material of valve seats	Stainless steel 316
Material of wetted parts	Aluminium
Max suction lift - Dry	5.9 m
Max suction lift - Wet	9 m
Max. Flow Rate	470 LPM
Max. Size Of Suspended Solids	6.4 mm
Net Dimensions	455.5mm x 326mm x 517.5mm
Net Weight	22 kg
Operating Pressure	1.5 - 8 bar
Pump size	1.5"
Pump type	Metallic
Tariff code	8413508090

Type	Standard Pump
------	---------------