

SAMOA 3" PNEUMATIC DIAPHRAGM PUMP

Metallic

UP30A-BAC-ATZ
UP30, AODD Pump, 3", Aluminium, Teflon, 1000 LPM,
ATEX

- Pump Size 3"
- Connection Types - BSP/NPT Center Ports, ANSI/DIN Center Flange
- Max. Flow Rate 1000 LPM
- Operating Pressure 1.5 - 8 bar

PRODUCT DESCRIPTION

TECHNICAL DATA

Approvals	CE ATEX, UKCA, EAC
Country of origin	Spain
Diaphragm Type	2-Piece
Fluid Displacement Per Cycle	10 litres
Fluid Port Connection Type	BSP Center Ports
Material Air Section (Central Body & Air cover)	Aluminium
Material Of Diaphragm	PTFE
Material of valve ball	PTFE
Material of valve seats	Aluminium
Material of wetted parts	Aluminium
Max suction lift - Dry	6 m
Max suction lift - Wet	8 m
Max. Flow Rate	1000 LPM
Max. Size Of Suspended Solids	12.7 mm
Net Dimensions	575mm x 436mm x 820mm
Net Weight	64 kg
Operating Pressure	1.5 - 8 bar
Pump size	3"
Pump type	Metallic

Tariff code

8413508090

Type

Key Model Pump