

SAMOA 3" PNEUMATIC DIAPHRAGM PUMP

Metallic

UP30A-BAC-MMA
UP30, AODD Pump, 3", Aluminium, Santoprene, 1000 LPM, ATEX

- Pump Size 3"
- Connection Types - BSP/NPT Center Ports, ANSI/DIN Center Flange
- Max. Flow Rate 1000 LPM
- Operating Pressure 1.5 - 8 bar

PRODUCT DESCRIPTION

TECHNICAL DATA

Approvals	CE ATEX, UKCA, EAC
Country of origin	Spain
Diaphragm Type	Convoluted
Fluid Displacement Per Cycle	10 litres
Fluid Port Connection Type	BSP Center Ports
Material Air Section (Central Body & Air cover)	Aluminium
Material Of Diaphragm	Santoprene
Material of valve ball	Santoprene
Material of valve seats	Santoprene
Material of wetted parts	Aluminium
Max suction lift - Dry	6 m
Max suction lift - Wet	8 m
Max. Flow Rate	1000 LPM
Max. Size Of Suspended Solids	12.7 mm
Net Dimensions	575mm x 436mm x 820mm
Net Weight	64 kg
Operating Pressure	1.5 - 8 bar
Pump size	3"
Pump type	Metallic

Tariff code	8413508090
Type	Key Model Pump