

NAFSA - ER SERIES

ER15/C
ER15/C

- Single acting, spring or load return
- Up to class F winding (155°C)
- Duty cycle from 0 to 100%
- Up to 234N force
- Customer specific version available



PRODUCT DESCRIPTION

The ER series of electromagnets are a single acting solenoid.

When an electrical connection is made to the coil, the plunger moves through the magnetic field and pushes the shaft along its designated stroke.

Upon removing the electrical connection, the shaft is retracted to its rest position using either a mechanical spring or the load applied.

Many different standard versions are available (please see catalogue PDF below) and application specific designs can be provided for larger volume requirements.

TECHNICAL DATA

Absorbed power @ 20°C, 100% duty	3 W
Absorbed power @ 20°C, 15% duty	20 W
Absorbed power @ 20°C, 25% duty	12 W
Absorbed power @ 20°C, 40% duty	7.5 W
Absorbed power @ 20°C, 5% duty	60 W
Beginning of stroke force at 100% duty	0.3 N
Beginning of stroke force at 15% duty	1 N
Beginning of stroke force at 25% duty	0.8 N
Beginning of stroke force at 40% duty	0.5 N
Beginning of stroke force at 5% duty	2.5 N
End of stroke force at 100% duty	4.9 N
End of stroke force at 15% duty	12.2 N
End of stroke force at 25% duty	9.8 N
End of stroke force at 40% duty	7.9 N

End of stroke force at 5% duty	16.5 N
Function	pull/push
Insulation class	B (130°C)
IP class	IP00
Spring return	No
Total weight	39 g
Voltage ac max	230 V
Voltage ac min	110 V
Voltage dc max	205 V
Voltage dc min	6 V

Duty-cycle ED%	Standard voltages								Under demand voltages					
	VDC								VAC		VDC		VAC	
	6	12	24	48	100	125	205	110	230	Min	Max	Min	Max	
100%	o	o	o	o	o	x	x	x	x	3	55	x	x	
40%	o	o	o	o	x	x	x	x	x	3	85	x	x	
25%	o	o	o	o	o	x	x	x	x	3	105	x	x	
15%	o	o	o	o	o	o	x	x	x	6	135	x	x	
5%	o	o	o	o	o	o	o	x	x	6	230	x	x	
Layout:	o = Available ; x = Unavailable													

