

## NAFSA - ECM SERIES

ECM13-03/T

- Pull / push design, with optional spring
- Class B winding (130°C)
- Round profile for panel mounting
- Up to 32N force
- Customer specific version available



### PRODUCT DESCRIPTION

The ECM series is simple linear solenoid where the stroke movement from start to final position is made by the electromagnetic forces.

Return to start position is done by external forces or of a spring built into the solenoid.

The front end design is ideally suited to panel mounting.

### TECHNICAL DATA

Absorbed power @ 20°C, 100% duty	1 W
Absorbed power @ 20°C, 15% duty	6.6 W
Absorbed power @ 20°C, 25% duty	4 W
Absorbed power @ 20°C, 40% duty	2.5 W
Absorbed power @ 20°C, 5% duty	20 W
Beginning of stroke force at 100% duty	0.02 N
Beginning of stroke force at 15% duty	0.2 N
Beginning of stroke force at 25% duty	0.12 N
Beginning of stroke force at 40% duty	0.08 N
Beginning of stroke force at 5% duty	0.5 N
End of stroke force at 100% duty	0.15 N
End of stroke force at 15% duty	1 N
End of stroke force at 25% duty	0.69 N
End of stroke force at 40% duty	0.43 N
End of stroke force at 5% duty	2.29 N

