

OEM Automatic Ltd

Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

MRS LINEAR GUIDE

MRS15-100 MRS Sliding Type, 100mm, 2 Holes, 14.5g, Aluminium Alloy, Static Rated Load,



- · Does not need grease
- · Very compact
- · high corrosion resistance

PRODUCT DESCRIPTION


The Sugatsune MRS Sliding Type is a high-performance sliding door system designed to deliver smooth, quiet, and reliable operation. Featuring a compact, low-profile design, it offers a clean, minimalist aesthetic ideal for modern interiors. Precision-engineered with ball-bearing rollers, the MRS system ensures effortless and silent movement, even with heavier door panels. Its construction emphasises both durability and functionality, making it suitable for high-traffic environments in residential, commercial, and architectural settings.


This versatile system includes adjustable components for easy installation across various door sizes and configurations. Many models in the MRS line also incorporate soft-close technology, enhancing user safety and delivering a refined closing motion. Whether used in cabinetry, closet doors, or room partitions, the Sugatsune MRS Sliding Type exemplifies Japanese craftsmanship, providing a seamless blend of form and function for design-conscious projects.

TECHNICAL DATA

Feature	MRS Sliding Type
Guide Block Length	20 mm
Guide Block Screw Size	M3
Horizontal Load FX	100 N
Load Type	Static Rated Load
Material	Aluminium alloy
Number of holes	2
Rail & Guide Block Height	7 mm
Rail & Guide Block Width	15 mm
Rail Hole Pitch	50 mm
Rail Length	100 mm
Rail Screw Size	M3
Rail Width	15 mm
Surface finish	Silver Anodised
Weight	14.5 g
Vertical Load FY	30 N

Load Direction





Load Direction

