

## **OEM Automatic Ltd**

Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

## **SCRW-15S LINEAR SLIDES**

SCRW2-15S-150A All Stainless Steel, 2-Way Mini Slide, 150mm, 94.5mm Travel

- 3/4 Extension
- All Stainless Steel
- · Short height makes is suitable for reduced spaces




## PRODUCT DESCRIPTION

The Sugatsune SCRW2-15S Linear Slide is a high-precision, two-member, %-extension slide engineered in durable stainless steel (SUS 304). With an ultra-slim 15.5 mm profile and minimal deflection, it's ideal for tight installations in furniture, cabinetry, industrial machinery, or marine environments. Available in three slide-length options, with load capacities of 14–18 kg per pair, make it capable of handling moderate loads with smooth and reliable motion. The slide is side-mountable, non-handed, and features RoHS 3 compliance.

Practically, the SCRW2-15S series excels in environments demanding both compact form and clean operation. In professional kitchens, laboratory drawer systems, medical carts, or marine vessels, its all-stainless construction resists corrosion while its food-grade lubrication ensures cleanliness and compliance. The slide's low-deflection, thin profile allows installation in narrow gaps—particularly useful for embedded drawers or slim pull-outs—while its two-way travel enables opening in either direction, enhancing flexibility in bespoke furniture design or machine access panels. Overall, the SCRW2-15S is a compact, hygienic, and versatile solution for precision linear motion in demanding or space-constrained applications.


## **TECHNICAL DATA**

Back Travel Length	94.5 mm
Feature	2-Way Mini Slide
Front Travel Length	94.5 mm
Height	15.5 mm
Load Capacity Per Pair	177 N
Material	Stainless steel
Rail Length	150 mm
Rail Width	5.2 mm
Weight	41 g



No.	Part Name	Material
1	Outer Member	Otainlana Otani
2	Inner Member	Stainless Steel
3	Retainer	(SUS304)
4	Balls	Stainless Steel (SUS440)

us	<b></b>		Item Name	Stide Length	Travel Length			ш	10			100	Vertical Installation		Weight	Вок	Carton
	33				Front	Back	•	AB	B C	D	151	851	Load Capacity Nipel	Load Capacity lightyer	(g/px) (pex)	(9414)	(pex)
ï		190-034-806	SCRW2-15S-80A	80	48.5	48.5	56	-	28	56	-	32	137	14	21		-
ï	23	190-034-807	SCRW2-15S-100A	100	68.5	66.5	76	38	48	76	38	52	167	16	26		-
ï	8	190-034-608	SCRW2-15S-150A	150	94.5	94.5	126	63	98	126	63	102	177	18	41		-



No.	Part Name	Material
1	Outer Member	Otainlana Otani
2	Inner Member	Stainless Steel
3	Retainer	(SUS304)
4	Balls	Stainless Steel (SUS440)

	<b>100</b>		Bem Name	Stide Length	Travel Length			æ	ΗŒ			100	Vertical Installation		Weight	Box	Carto
**	w				Front	Back	10	400	18	100	100		Lead Capacity Nipel'	<b>Seed Capacity tigSpair</b>	(994)	(944)	(pex)
30	8	190-034-806	SCRW2-15S-80A	80	48.5	48.5	66		28	56		32	137	54	21		
33	8	190-034-807	SCRW2-15S-100A	100	68.5	68.5	76	38	48	76	38	52	157	16	26		-
89	8	190-034-808	SCRW2-15S-150A	150	94.5	94.5	126	63	98	126	63	102	177	18	41	-	-