

OEM Automatic Ltd

Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

SCRL-15S LINEAR SLIDE

SCRL2-15S-80A Fully Stainless Steel Mini Guide, 80mm, 49mm Travel

- Small Deflection Suitable For Various Places
- · Fully Stainless Steel
- · Various Lengths Available




PRODUCT DESCRIPTION

The SCRL2-15S is a fully stainless steel mini-guide linear slide with an ultra-slim 15.5 mm profile and low deflection, perfect for tight installation spaces. Crafted from SUS 304 stainless steel and equipped with smooth ball-bearing action, the slide comes pre-lubricated using NSF H1 registered food-grade grease, ideal for hygienic environments. It's available in a range of closed lengths (80 mm, 100 mm, 150 mm, 200 mm), with load capacities varying from approximately 18 kg to 24 kg per pair and features side-mount, non-handed design compliant with RoHS 3.

Practically, the SCRL2-15S excels wherever space is at a premium and cleanliness matters, such as in food-processing equipment, laboratory drawers, medical carts, and marine or industrial cabinetry. Its stainless construction ensures strong corrosion resistance and easy maintenance, while the slim form enables elegant, discrete integration into compact applications like point-of-sale devices, instrument panels, and compact storage systems.


TECHNICAL DATA

Feature	Mini Guide
Height	15.5 mm
Load Capacity Per Pair	177 N
Material	Stainless steel
Rail Length	80 mm
Rail Width	5.2 mm
Travel Length	49 mm
Weight	16 g



No.	Part Name	Material					
0	Outer Member						
(2)	Inner Member	Stainless Steel (SUS304)					
3	Retainer	The state of the s					
4	Balls	Stainless Steel (SUS440)					

	CAZ		Tem Name	Slide	Travel Length	A	45S	霺	D			G	н	Vertical I	Weight	Box	Carton	
•	2			Length			18	10						Lead Capacity Nipels	Load Capacity lightput	(p/pc)	(pcs)	(pcs)
ū	8	190-034-809	SCRL2-15S-80A	80	49	28	18				56		32	127	18	16		-
ä	8	190-034-810	SCRL2-15S-100A SCRL2-15S-150A	100	59						70	38	52	206	21	20		-
ū	2	190-034-811	SCRL2-15S-150A	150	109	100	100	1.0	14	14	126	63	102	200	- 41	29		-
ũ	8	190-034-812	SCRL2-159-200A	200	149	48	38	10	14	14	576	88	152	235	24	38	-	



No.	Part Name	Material					
0	Outer Member						
(2)	Inner Member	Stainless Steel (SUS304)					
3	Retainer	The state of the s					
4	Balls	Stainless Steel (SUS440)					

000				Slide	Travel									Vertical Installation Leel Death Nor Leel Ceach ighai		Weight	Box	Carton
200	000														Load Capacity lightput	(p/pc)	(pcs)	(pcs)
33	8	190-034-809	SCRL2-15S-80A	80	49	28	18				56		32	177	18	16		-
39	8	190-034-810	SCRL2-15S-100A SCRL2-15S-150A	100	59						70	38	52	206	21	20		
30	2	190-034-811	SCRL2-15S-150A	150	109	100	38 28	1.0	12	19	126	63 102	200	- 41	29	-	-	
74	8	190-034-812	SCRL2-15S-200A	200	149	45	38	10	14	14	176	88	152	235	24	38	-	