OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

NXT-D-050 PLANETARY GEARBOX

Inline direct drive gearbox

NXT-D-050-2-81



- 50mm diameter, high efficiency
- Very high torsional stiffness
- Low std backlash with tighter tolerance option
- Nominal torque up to 12Nm
- Ratios 3:1 to 81:1

PRODUCT DESCRIPTION

NXT D series range offers coaxial planetary gearboxes in 4 sizes with high torsional rigidity and standard keyway output shaft.

• Gear ratios from 3:1 (single stage) to 100:1 (two stage)
• Nominal torque handling from 8-110Nm
• Torsional rigidity between 0.7-22Nm/arcmin

Two backlash tolerances are available in each configuration depending on application requirements.
NXT range also includes right-angle and toothed pulley-drive output options, IP65 is standard

TECHNICAL DATA

1651_Moment of inertia (kg/cm²)	0,07
Axial load max	450 N
Efficiency	93 %
Emergency brake torque	25
Input speed	3800 rpm
IP class	IP65
Max backlash	12 arcmin
Max radial load	500 N
Max. input speed	6000 rpm
Noise level	70 dB
Nominal torque	9.5
Reduction ratio	81
Starting torque	15
Stiffness	0.7 Nm/arcmin
Weight	0.95 kg