0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

## **NXT-D-120 PLANETARY GEARBOX**

Inline direct drive gearbox

NXT-D-120-1-10

- 120mm diameter, high efficiency
- Very high torsional stiffness
- · Low std backlash with tighter tolerance option
- Nominal torque up to 110Nm
- Ratios 3:1 to 100:1



## PRODUCT DESCRIPTION

NXT D series range offers coaxial planetary gearboxes in 4 sizes with high torsional rigidity and standard keyway output shaft.

- Gear ratios from 3:1 (single stage) to 100:1 (two stage)
- Nominal torque handling from 8-110Nm
- Torsional rigidity between 0.7-22Nm/arcmin

Two backlash tolerances are available in each configuration depending on application requirements.

NXT range also includes right-angle and toothed pulley-drive output options, IP65 is standard

## **TECHNICAL DATA**

| Axial load max         | 3800 N       |
|------------------------|--------------|
| Efficiency             | 96 %         |
| Emergency brake torque | 350          |
| Input speed            | 2600 rpm     |
| IP class               | IP65         |
| Max backlash           | 8 arcmin     |
| Max radial load        | 4500 N       |
| Max. input speed       | 5000 rpm     |
| Moment of inertia      | 5.09         |
| Noise level            | 72 dB        |
| Nominal torque         | 95           |
| Reduction ratio        | 10           |
| Starting torque        | 190          |
| Stiffness              | 20 Nm/arcmin |



Weight 8 kg