OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

NXT-D-120 PLANETARY GEARBOX

Inline direct drive gearbox

NXT-D-120-1-10



- 120mm diameter, high efficiency
- Very high torsional stiffness
- Low std backlash with tighter tolerance option
- Nominal torque up to 110Nm
- Ratios 3:1 to 100:1

PRODUCT DESCRIPTION

NXT D series range offers coaxial planetary gearboxes in 4 sizes with high torsional rigidity and standard keyway output shaft.

• Gear ratios from 3:1 (single stage) to 100:1 (two stage)
• Nominal torque handling from 8-110Nm
• Torsional rigidity between 0.7-22Nm/arcmin

Two backlash tolerances are available in each configuration depending on application requirements.
NXT range also includes right-angle and toothed pulley-drive output options, IP65 is standard

TECHNICAL DATA

1651_Moment of inertia (kg/cm²)	5.09
Axial load max	3800 N
Efficiency	96 %
Emergency brake torque	350
Input speed	2600 rpm
IP class	IP65
Max backlash	8 arcmin
Max radial load	4500 N
Max. input speed	5000 rpm
Noise level	72 dB
Nominal torque	95
Reduction ratio	10
Starting torque	190
Stiffness	20 Nm/arcmin
Weight	8 kg