

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

NXT-D-120 PLANETARY GEARBOX

Inline direct drive gearbox

NXT-D-120-2-20

- 120mm diameter, high efficiency
- Very high torsional stiffness
- · Low std backlash with tighter tolerance option
- Nominal torque up to 110Nm
- Ratios 3:1 to 100:1



PRODUCT DESCRIPTION

NXT D series range offers coaxial planetary gearboxes in 4 sizes with high torsional rigidity and standard keyway output shaft.

- Gear ratios from 3:1 (single stage) to 100:1 (two stage)
- Nominal torque handling from 8-110Nm
- Torsional rigidity between 0.7-22Nm/arcmin

Two backlash tolerances are available in each configuration depending on application requirements.

NXT range also includes right-angle and toothed pulley-drive output options, IP65 is standard

TECHNICAL DATA

Avial land way	2000 N
Axial load max	3800 N
Efficiency	94 %
Emergency brake torque	400
Input speed	2600 rpm
IP class	IP65
Max backlash	12 arcmin
Max radial load	4500 N
Max. input speed	5000 rpm
Moment of inertia	5.29
Noise level	72 dB
Nominal torque	110
Reduction ratio	20
Starting torque	210
Stiffness	22 Nm/arcmin



Weight 10.5 kg