

## NXT-P-120 PLANETARY GEARBOX

Inline pulley drive gearbox

NXT-P-120-1-3

- 120mm diameter, high efficiency
- Pulley output planetary gearbox
- Low std backlash with tighter tolerance option
- Nominal torque up to 110Nm
- Ratios 3:1 to 100:1



### PRODUCT DESCRIPTION

NXT P series range offers coaxial planetary gearboxes in 3 sizes with high torsional rigidity and toothed-pulley output shaft.

- Gear ratios from 3:1 (single stage) to 100:1 (two stage)
- Nominal torque handling from 16.5-110Nm
- Torsional rigidity between 2.8-22Nm/arcmin

Two backlash tolerances are available in each configuration depending on application requirements. NXT range also includes in-line and right-angle output options with keyway shaft, IP65 is standard.

### TECHNICAL DATA

1651_Moment of inertia (kg/cm <sup>2</sup> )	6.9
Axial load max	3800 N
Efficiency	96 %
Emergency brake torque	350
Input speed	2600 rpm
IP class	IP65
Max backlash	6 arcmin
Max radial load	9500 N
Max. input speed	5000 rpm
Noise level	72 dB
Nominal torque	95
Reduction ratio	3
Starting torque	190
Stiffness	30 Nm/arcmin
Weight	8 kg

