

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

## **NXT-P-120 PLANETARY GEARBOX**

Inline pulley drive gearbox

NXT-P-120-1-5

- 120mm diameter, high efficiency
- Pulley output planetary gearbox
- · Low std backlash with tighter tolerance option
- Nominal torque up to 110Nm
- Ratios 3:1 to 100:1



## PRODUCT DESCRIPTION

NXT P series range offers coaxial planetary gearboxes in 3 sizes with high torsional rigidity and toothed-pulley output shaft.

- Gear ratios from 3:1 (single stage) to 100:1 (two stage)
- Nominal torque handling from 16.5-110Nm
- Torsional rigidity between 2.8-22Nm/arcmin

Two backlash tolerances are available in each configuration depending on application requirements. NXT range also includes in-line and right-angle output options with keyway shaft, IP65 is standard.

## **TECHNICAL DATA**

Axial load max	3800 N
Axiai loau max	3000 IN
Efficiency	96 %
Emergency brake torque	400
Input speed	2600 rpm
IP class	IP65
Max backlash	6 arcmin
Max radial load	9500 N
Max. input speed	5000 rpm
Moment of inertia	5.69
Noise level	72 dB
Nominal torque	110
Reduction ratio	5
Starting torque	210
Stiffness	35 Nm/arcmin

Weight 8 kg