OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

NXT-P-120 PLANETARY GEARBOX

Inline pulley drive gearbox

NXT-P-120-2-35



- 120mm diameter, high efficiency
- Pulley output planetary gearbox
- Low std backlash with tighter tolerance option
- Nominal torque up to 110Nm
- Ratios 3:1 to 100:1

PRODUCT DESCRIPTION

NXT P series range offers coaxial planetary gearboxes in 3 sizes with high torsional rigidity and toothed-pulley output shaft.

• Gear ratios from 3:1 (single stage) to 100:1 (two stage)
• Nominal torque handling from 16.5-110Nm
• Torsional rigidity between 2.8-22Nm/arcmin

Two backlash tolerances are available in each configuration depending on application requirements.
NXT range also includes in-line and right-angle output options with keyway shaft, IP65 is standard.

TECHNICAL DATA

1651_Moment of inertia (kg/cm²)	5.09
Axial load max	3800 N
Efficiency	94 %
Emergency brake torque	400
Input speed	2600 rpm
IP class	IP65
Max backlash	8 arcmin
Max radial load	9500 N
Max. input speed	5000 rpm
Noise level	72 dB
Nominal torque	110
Reduction ratio	35
Starting torque	210
Stiffness	35 Nm/arcmin
Weight	10.5 kg