

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

## **NXT-A-070 SERIES**

Right-angle planetary gearbox

NXT-A-070-1-4

- 70mm diameter, high efficiency
- Very high torsional stiffness
- · Low std backlash with tighter tolerance option
- Nominal torque up to 20Nm
- Ratios 3:1 to 100:1



## PRODUCT DESCRIPTION

NXT A series range offers right-angle planetary gearboxes in 3 sizes with high torsional rigidity and standard keyway output shaft.

- Gear ratios from 3:1 (single stage) to 100:1 (two stage)
- Nominal torque handling from 16.5-110Nm
- Torsional rigidity between 2.8-22Nm/arcmin

Two backlash tolerances are available in each configuration depending on application requirements.

NXT range also includes in-line and toothed pulley-drive output options, IP65 is standard.

## **TECHNICAL DATA**

| Axial load max         | 1500 N        |
|------------------------|---------------|
| Efficiency             | 94 %          |
| Emergency brake torque | 60            |
| Input speed            | 3000 rpm      |
| IP class               | IP65          |
| Max backlash           | 8 arcmin      |
| Max radial load        | 1400 N        |
| Max. input speed       | 4500 rpm      |
| Moment of inertia      | 0.42          |
| Noise level            | 73 dB         |
| Nominal torque         | 16            |
| Reduction ratio        | 4             |
| Starting torque        | 30            |
| Stiffness              | 2.8 Nm/arcmin |



Weight 2.3 kg