

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

NXT-A-070 SERIES

Right-angle planetary gearbox

NXT-A-070-2-25

- 70mm diameter, high efficiency
- Very high torsional stiffness
- · Low std backlash with tighter tolerance option
- Nominal torque up to 20Nm
- Ratios 3:1 to 100:1



PRODUCT DESCRIPTION

NXT A series range offers right-angle planetary gearboxes in 3 sizes with high torsional rigidity and standard keyway output shaft.

- Gear ratios from 3:1 (single stage) to 100:1 (two stage)
- Nominal torque handling from 16.5-110Nm

Torsional rigidity between 2.8-22Nm/arcmin

Two backlash tolerances are available in each configuration depending on application requirements. NXT range also includes in-line and toothed pulley-drive output options, IP65 is standard.

TECHNICAL DATA

| Axial load max | 1500 N |
|------------------------|-------------|
| Efficiency | 91 % |
| Emergency brake torque | 70 |
| Input speed | 3000 rpm |
| IP class | IP65 |
| Max backlash | 12 arcmin |
| Max radial load | 1400 N |
| Max. input speed | 4500 rpm |
| Moment of inertia | 0.39 |
| Noise level | 73 dB |
| Nominal torque | 20 |
| Reduction ratio | 25 |
| Starting torque | 35 |
| Stiffness | 3 Nm/arcmin |



Weight