OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

NXR-105 PLANETARY GEARBOX

High torque tranmission version

NXR-105-2-100



- 105mm diameter, modular design, customisable
- Very high torsional stiffness
- Low std backlash with tighter tolerance option
- Nominal torque up to 155Nm
- Ratios 3:1 to 100:1

PRODUCT DESCRIPTION

NXR series offers coaxial planetary gearboxes in 3 sizes, this range provides very high torque transfer along with excellent torsional rigidity. Many aspects of this gearbox range can be customised to suit the specific requirements of the application, as standard there is keyway output shaft.

• Gear ratios from 3:1 (single stage) to 100:1 (two stage)
• Nominal torque handling from 8-110Nm
• Torsional rigidity between 0.7-22Nm/arcmin

Two backlash tolerances are available in each configuration depending on application requirements. IP65 is standard.

TECHNICAL DATA

1651_Moment of inertia (kg/cm²)	4.97
Axial load max	4000 N
Efficiency	94 %
Emergency brake torque	350
Input speed	2600 rpm
IP class	IP65
Max backlash	12 arcmin
Max radial load	3800 N
Max. input speed	5000 rpm
Noise level	72 dB
Nominal torque	95
Reduction ratio	100
Starting torque	95
Stiffness	20 Nm/arcmin
Weight	10.5 kg