

DATA SENSING - S300-PR - MAXI SENSOR RELAY OUTPUT

S300-PR-1-M06-RX-M
 951451200 BGS w/ Timer ac/dc Relay Terminal Block
 Defog

- Long detection distances
- M12 contact or terminal connection
- Temperature range -40° to +55°C
- AC and DC versions
- Relay Output



PRODUCT DESCRIPTION

The advanced line of S300 maxi photoelectric sensors is the most suitable solution for critical applications thanks to the excellent performances and resistance to the harsh use conditions. The series offers a wide range of models and optical functions, able to meet the most demanding customer needs. The S300 series is available in 4 different models with through beam optical function up to 60m, polarized retro reflective at 20m, diffused proximity at 3m and background suppression at 2.5m. All models are available with both Vdc from 10 to 30V and Vac/Vdc free-voltage from 24 to 240V versions, also with timing function version and defogging system.

Features & Benefits:

- Simple and complete User Interface for timing functions: easy and fast setting
- Swivelling connector block: to improve installation capability and to adapt the sensor to the mechanical parts of the machine
- Sensor housing in only one structure with fibre loading: to improve housing toughness and guarantee plant reliability
- Excellent operating distance: to guarantee high application flexibility
- ALARM output and TEST input: to improve both the reliability and process production of the plant avoiding to stop the plant
- Defogging system: to avoid lens condensation and to improve both the reliability and process production of the plant

Applications:

- Automatic machines
- Transportation lines
- Wood working machines
- Automatic warehouses

TECHNICAL DATA

Anti-fog function	Yes
Approvals	CE, UL
Dimension (mm)	25 x 100 x 70
Distance max	2500 mm
Distance min	400 mm

Electrical connection	Terminal
Frequency	25 Hz
IP class	IP67
LED indicator	Yes
Lens material	PC
Light type	IR LED
Material of body	Glass fiber reinforced plastic (PBT)
Output	Relay
Output current max	3 A
Photocell technology	Background suppression
Reaction time	20 ms
Sensitivity setting	Yes
Storage temperature max	70 °C
Storage temperature min	-40 °C
Supply voltage	24-240 V AC/24-60 V DC
Temperature operational max	55 °C
Temperature operational min	-40 °C
Type of light	LED
Weight	150 g

