

## GELBAU - CONTROL UNIT 452.4/462.4

3004.6246

Resistance Evaluator Cat3. 2 Input, 2x NO, 1x CO Cont.  
24Vdc

- 2 NO+1 CO output
- Safety category 3 in accordance with EN954-1
- Automatic or manual reset
- Available with variable supply voltage



### PRODUCT DESCRIPTION

Compact control unit with only 22.5 mm enclosure for the monitoring of sensing strips in dangerous applications. It is also suitable for use on motorised gates which, in line with the standard, must have relays conforming to safety category 3. A low current is transmitted from the control unit connectors (Z1 and Z2) through the sensing strip, and a closed circuit is formed via a resistor (8.2 kΩ). The control unit's outputs cut the power if anyone/anything presses the sensing strip and also following a short-circuit or open circuit.

### TECHNICAL DATA

Approvals	CE, TÜV NORD
Cable length to clip list max	50 m (min. 0,5 m2)
Contact current max	4 A AC/DC
Contact voltage max	250 V AC/24 V DC
Disconnection	15 ms
Fuse output	4 A
In compliance with	EMC, LVD, MD
IP class connection	IP20
IP class of housing	IP40
Mounting	DIN rail
PL	e enl. SS-EN ISO 13849-1:2008
Power consumption	3 W
Supply voltage	24 V DC

Temperature ambient from -20 °C

Temperature ambient to 55 °C

Terminal strip length max 100 m

Tolerance max 10 %

Tolerance min -15 %



