



SUCO - 0180/0181 PRESSURE SWITCH

Long service life

0180457031003
0,3..1,5 bar, G1/4, CO, NBR, Spade

- Up to 250 V
- Spade terminals
- Five adjustment ranges from 0.3-1.5 bar to 50-200 bar
- Changeover (SPDT)
- Over pressure safety from 100 bar up to 600 bar



PRODUCT DESCRIPTION

The 0180/0181 series is a compact pressure switch and is part of the changeover contact range from SUCO. Offering a maximum voltage of 250 V with a normally open and normally closed contact housed in a hex 27 zinc plated body offering a high pressure resistance. The switch point is very stable even after a long period of time and high load and is also adjustable on site and can come pre-set.

Common applications include power packs, mobile hydraulics, water systems, hydraulics generally and pneumatics.

TECHNICAL DATA

| | |
|--------------------------|-------------------------------|
| Adjustment range max | 1,5 bar |
| Adjustment range min | 0,3 bar |
| Approvals | CSA US, RoHS II |
| Contact load max ac | 4 A |
| Contact load max dc | 0,25 A |
| Deviation max | ±0,2 |
| Electrical connection | Spade (AMP 6,3x0,8 mm) |
| Function | Changeover (SPDT) |
| Hysteresis | 10-30% depending on set value |
| IP class | IP00 |
| Material membrane | NBR |
| Material of body | Galvanized steel |
| Material of wetted parts | Galvanized steel, NBR |

| | |
|-----------------------------|---------------------|
| Max switching frequency/min | 200 |
| Mechanical life expectancy | 1 million exchanges |
| Pressure max | 100 bar |
| Pressure range max | 1,5 bar |
| Pressure range min | 0,3 bar |
| Pressure type | Relativt tryck |
| Process connection | 1/4 BSP |
| Temperature ambient from | -20 °C |
| Temperature ambient to | 80 °C |
| Temperature of media from | -30 °C |
| Temperature of media to | 100 °C |
| Type Pressure Switch | High accuracy |
| Weight | 100 g |
| Voltage ac/dc max | 250 V |
| Voltage ac/dc min | 10 V |

