



SUCO - 0166/0169 PRESSURE SWITCH

Compact design

0166421033070

0,5..3 bar, G1/4, No, FKM, Screw

- Up to 42 V
- Spade or screw terminals
- Six adjustment ranges from 0,1..1 bar to 50..150 bar
- Normally open or normally closed
- Overpressure safety of 300 bar or 600 bar



PRODUCT DESCRIPTION

The 0166/0169 series pressure switch is the most cost effective solution from SUCO for mechanical pressure monitoring. Offering a maximum voltage of 42V with normally open or normally closed contacts housed in a hex 24 zinc plated body offering a high pressure resistance. The switch point is very stable even after a long period of time and high load and is also adjustable on site and can come pre-set.

Common applications include power packs, mobile hydraulics, water systems, hydraulics generally and pneumatics.

TECHNICAL DATA

| | |
|-----------------------------|-----------------------|
| Adjustment range max | 3 bar |
| Adjustment range min | 0.5 bar |
| Approvals | CSA US, RoHS II |
| Contact rating max | 4 A |
| Deviation max | ±0,3 |
| Electrical connection | Screw (M3) |
| Function | Normally open (SPST) |
| IP class | IP00 |
| Material membrane | FKM |
| Material of body | Galvanized steel |
| Material of wetted parts | FKM, Galvanized steel |
| Max switching frequency/min | 200 |

| | |
|----------------------------|---------------------|
| Mechanical life expectancy | 1 million exchanges |
| Pressure max | 400 bar |
| Process connection | 1/4 BSP |
| Temperature ambient from | -20 °C |
| Temperature ambient to | 80 °C |
| Temperature of media from | -5 °C |
| Temperature of media to | 120 °C |
| Weight | 90 g |
| Voltage ac/dc max | 42 V |
| Voltage ac/dc min | 10 V |

