



## SUCO - 0340/0341 PRESSURE SWITCH

ATEX rated

0340458032006

1..10 bar, G1/4, CO, EPDM, 2M cable, EX

- Dust protected zone 22
- Up to 250 V
- Five adjustment ranges from 0,3..1,5 bar to 50..150 bar
- Changeover (SPDT)
- Overpressure safety of 300 bar or 600 bar



### PRODUCT DESCRIPTION

The 0340/0341 series pressure switch is part of the ATEX range from SUCO. Designed for dust protection zone 22 offering a maximum voltage of 250V with a normally open and normally closed contact housed in a hex 27 zinc plated body offering a high pressure resistance. The switch point is very stable even after a long period of time and high load and also adjustable on site and can come pre-set.

Common applications include process mills, refineries safe areas.

### TECHNICAL DATA

Adjustment range max	10 bar
Adjustment range min	1 bar
Approvals	CE, CSA US, Atex Ex II 3D IP65 T90°, RoHS II
Contact load max ac	2 A
Deviation max	±0,5-1,0
Electrical connection	Embedded 2m cable
Function	Changeover (SPDT)
IP class	IP65
Material membrane	EPDM
Material of body	Zinc-plated steel
Material of wetted parts	EPDM, Zinc-plated steel
Max switching frequency/min	200
Pressure max	300 bar

<b>Process connection</b>	1/4 BSP
<b>Shock resistance</b>	294m / s <sup>2</sup> ; 14 ms half sinusoidal wave; DIN EN 60068-2-27
<b>Temperature ambient from</b>	-20 °C
<b>Temperature ambient to</b>	80 °C
<b>Temperature of media from</b>	-20 °C
<b>Temperature of media to</b>	80 °C
<b>Weight</b>	230 g
<b>Vibration resistance</b>	10g: 5..200 Hz sine wave, DIN EN 60068-2-6
<b>Voltage ac max</b>	250 V
<b>Voltage ac min</b>	10 V

