



SUCO 0500/0501 ELECTRONIC PRESSURE SWITCH

Factory set

0501161412011
NC, 0 - 16 Bar, G 1/4, EPDM, Cable connection

- Single switch point
- Small & compact
- Ceramic sensor
- Stainless steel housing

PRODUCT DESCRIPTION

The SUCO 0500/0501 performance series electronic pressure switch offers a small compact electronic switch without compromising on quality which comes factory set (unadjustable by the user) with overpressure protection (up to 2x), has a long service life and is also attractively priced especially at high volumes. Using a ceramic sensor in thick film technology for a good operating temperature range and accuracy, there are six standard pressure ranges starting from 0.2 bar all the way up to 0.100 bar and a hysteresis of 1%-98%, available in normally open or normally closed with a PNP transistor output. The wetted parts are made of ceramic, stainless steel and either NBR, EPDM OR FKM ensuring excellent media compatibility, with six standard electrical connection options including Deutsch, DIN and M12 combined with two standard thread type options.

Customer specific solutions are also available on request.

Application examples

- Automotive
- Braking systems
- Medical
- Mobile hydraulics
- Off highway
- Off-shore
- Rail

TECHNICAL DATA

GENERAL DATA

Adjustment range max	16 bar
Adjustment range min	0 bar
Electrical connection	Embedded 2m cable
Process connection	G1/4
Function	Normally Closed (SPST)
Output	PNP
Burst pressure	60 bar
Pressure max	40 bar

TEMPERATURE & MATERIALS DATA

Temperature of media from	-30 °C
Temperature of media to	125 °C
Temperature ambient from	-30 °C
Temperature ambient to	100 °C
Material of body	Stainless steel 1.4305
Material of wetted parts	EPDM, Stainless steel 1.4305
Material membrane	EPDM

ADDITIONAL DATA

Supply voltage dc max	32 V DC
Supply voltage dc min	9.6 V DC
Pressure rise	≤ 1 bar/ms
Switching time	< 4 ms
Switching point adjustment range	3...100 % of adjustment range(full scale) nominal pressure, set at factory

Weight 80 g

SAFETY & APPROVALS

IP class IP67

Hysteresis 2...98% full scale, programmable at factory (maximum tolerance $\pm 1.0\%$ of adjustment range nominal pressure)

Shock resistance 500m / s²; 11 ms half sine wave; DIN EN 60068-2-27

Vibration resistance 20g: 4..2000 Hz sine wave, DIN EN 60068-2-6



EMC EMC 2014/30/EU; EN 61000-6-2:2005; EN 61000-6-3:2007

Accuracy $\pm 0.5\%$ of adjustment range (Full scale) at room temperature

Long term stability $\pm 0.1\%$ of adjustment range (full scale) per year

Mechanical life expectancy 5,000,000 pulsations at rise rates to 1,000 bar/s nominal pressure

Repeatability $\pm 0.1\%$ of adjustment range (full scale) nominal pressure



DIN EN 175301-803-A	M 12 - DIN EN 61076-2-101-A	ISO 15170-A1-4.1																														
<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>1</td><td>U_{12V}</td></tr> <tr><td>2</td><td>Gnd</td></tr> <tr><td>3</td><td>U_{5V}</td></tr> <tr><td>PE</td><td>PE</td></tr> </tbody> </table>	Pin	Assignment	1	U _{12V}	2	Gnd	3	U _{5V}	PE	PE	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>1</td><td>U_{12V}</td></tr> <tr><td>2</td><td>NC</td></tr> <tr><td>3</td><td>Gnd</td></tr> <tr><td>4</td><td>U_{5V}</td></tr> </tbody> </table>	Pin	Assignment	1	U _{12V}	2	NC	3	Gnd	4	U _{5V}	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>1</td><td>U_{12V}</td></tr> <tr><td>2</td><td>NC</td></tr> <tr><td>3</td><td>Gnd</td></tr> <tr><td>4</td><td>U_{5V}</td></tr> </tbody> </table>	Pin	Assignment	1	U _{12V}	2	NC	3	Gnd	4	U _{5V}
Pin	Assignment																															
1	U _{12V}																															
2	Gnd																															
3	U _{5V}																															
PE	PE																															
Pin	Assignment																															
1	U _{12V}																															
2	NC																															
3	Gnd																															
4	U _{5V}																															
Pin	Assignment																															
1	U _{12V}																															
2	NC																															
3	Gnd																															
4	U _{5V}																															
Ø 12 ■ - 60 mm without copper socket ■ - 77 mm with copper socket Order number: 013	Ø 12 ■ - 54 mm Order number: 002	Ø 12 ■ - 56 mm Order number: 004																														
AMP Supersaal 1.5P	Deutsch DT04-3P	Cable connection																														
<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>1</td><td>U_{12V}</td></tr> <tr><td>2</td><td>Gnd</td></tr> <tr><td>3</td><td>U_{5V}</td></tr> </tbody> </table>	Pin	Assignment	1	U _{12V}	2	Gnd	3	U _{5V}	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>A</td><td>U_{12V}</td></tr> <tr><td>B</td><td>Gnd</td></tr> <tr><td>C</td><td>U_{5V}</td></tr> </tbody> </table>	Pin	Assignment	A	U _{12V}	B	Gnd	C	U _{5V}	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>red</td><td>U_{12V}</td></tr> <tr><td>white</td><td>U_{5V}</td></tr> <tr><td>black</td><td>Gnd</td></tr> </tbody> </table>	Pin	Assignment	red	U _{12V}	white	U _{5V}	black	Gnd						
Pin	Assignment																															
1	U _{12V}																															
2	Gnd																															
3	U _{5V}																															
Pin	Assignment																															
A	U _{12V}																															
B	Gnd																															
C	U _{5V}																															
Pin	Assignment																															
red	U _{12V}																															
white	U _{5V}																															
black	Gnd																															
Ø 12 ■ - 60 mm Order number: 007	Ø 12 ■ - 61 mm Order number: 010	Ø 12 ■ - 47 mm (+ 25 mm bend offset) Cable length: 2 m Order number: 011																														
Thread code: 41	Thread code: 09																															



DIN EN 175301-803-A	M 12 - DIN EN 61076-2-101-A	ISO 15170-A1-4.1																														
<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>1</td><td>U_{12V}</td></tr> <tr><td>2</td><td>Gnd</td></tr> <tr><td>3</td><td>U_{5V}</td></tr> <tr><td>PE</td><td>PE</td></tr> </tbody> </table>	Pin	Assignment	1	U _{12V}	2	Gnd	3	U _{5V}	PE	PE	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>1</td><td>U_{12V}</td></tr> <tr><td>2</td><td>NC</td></tr> <tr><td>3</td><td>Gnd</td></tr> <tr><td>4</td><td>U_{5V}</td></tr> </tbody> </table>	Pin	Assignment	1	U _{12V}	2	NC	3	Gnd	4	U _{5V}	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>1</td><td>U_{12V}</td></tr> <tr><td>2</td><td>NC</td></tr> <tr><td>3</td><td>Gnd</td></tr> <tr><td>4</td><td>U_{5V}</td></tr> </tbody> </table>	Pin	Assignment	1	U _{12V}	2	NC	3	Gnd	4	U _{5V}
Pin	Assignment																															
1	U _{12V}																															
2	Gnd																															
3	U _{5V}																															
PE	PE																															
Pin	Assignment																															
1	U _{12V}																															
2	NC																															
3	Gnd																															
4	U _{5V}																															
Pin	Assignment																															
1	U _{12V}																															
2	NC																															
3	Gnd																															
4	U _{5V}																															
Ø 12 ■ - 60 mm without copper socket ■ - 77 mm with copper socket Order number: 013	Ø 12 ■ - 54 mm Order number: 002	Ø 12 ■ - 56 mm Order number: 004																														
AMP Supersaal 1.5P	Deutsch DT04-3P	Cable connection																														
<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>1</td><td>U_{12V}</td></tr> <tr><td>2</td><td>Gnd</td></tr> <tr><td>3</td><td>U_{5V}</td></tr> </tbody> </table>	Pin	Assignment	1	U _{12V}	2	Gnd	3	U _{5V}	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>A</td><td>U_{12V}</td></tr> <tr><td>B</td><td>Gnd</td></tr> <tr><td>C</td><td>U_{5V}</td></tr> </tbody> </table>	Pin	Assignment	A	U _{12V}	B	Gnd	C	U _{5V}	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>red</td><td>U_{12V}</td></tr> <tr><td>white</td><td>U_{5V}</td></tr> <tr><td>black</td><td>Gnd</td></tr> </tbody> </table>	Pin	Assignment	red	U _{12V}	white	U _{5V}	black	Gnd						
Pin	Assignment																															
1	U _{12V}																															
2	Gnd																															
3	U _{5V}																															
Pin	Assignment																															
A	U _{12V}																															
B	Gnd																															
C	U _{5V}																															
Pin	Assignment																															
red	U _{12V}																															
white	U _{5V}																															
black	Gnd																															
Ø 12 ■ - 60 mm Order number: 007	Ø 12 ■ - 61 mm Order number: 010	Ø 12 ■ - 47 mm (+ 25 mm bend offset) Cable length: 2 m Order number: 011																														
Thread code: 41	Thread code: 09																															