



SUCO 0510/0511 G1/4 ELECTRONIC PRESSURE SWITCH

Adjustable by user

0511400411011

NC, 0 - 4 Bar, G 1/4, NBR, Cable connection

- Single switch point
- Small & compact
- Ceramic sensor
- Stainless steel housing

PRODUCT DESCRIPTION

The SUCO 0510 (NO) and 0511 (NC) models are compact, user-adjustable electronic pressure switches in a robust stainless-steel housing, featuring a 1/4-inch G1/4 process connection. They incorporate a ceramic thick-film pressure sensor and PNP transistor output, operating on 9.6–32 VDC with built-in reverse-polarity and short-circuit protection. The adjustable switching range spans from 0–2 bar up to 0–250 bar, with default hysteresis between 2–98% of full scale, and an impressive accuracy of ± 0.5 % FS. Overpressure resilience is rated at 2× nominal range, and burst resistance reaches up to 500 bar. With <4 ms switching response, mechanical durability of 5 million cycles, IP65–IP67 protection (depending on connector), and EMC compliance, these switches excel in reliability and longevity.

These switches are ideal for hydraulic, pneumatic, and fluid monitoring applications where space is limited, but precision and adjustability are essential—think mobile hydraulics, industrial compressors, and OEM machinery. External set-screw enables easy field adjustment, while the broad connector options (DIN EN 175301, M12, Superseal, Deutsch) simplify integration into varied control systems. Users benefit from ceramic sensor stability, low temperature drift (~ 0.04 % FS/°C), and repeatability (± 0.1 %), making them suitable for tasks like pressure safety cut-offs, pump control, and system diagnostics.

TECHNICAL DATA

GENERAL DATA

Adjustment range max	4 bar
Adjustment range min	0 bar
Electrical connection	Embedded 2m cable
Process connection	G1/4
Function	Normally Closed
Output	PNP
Burst pressure	20 bar
Pressure max	10 bar

TEMPERATURE & MATERIALS DATA

Temperature of media from	-30 °C
Temperature of media to	100 °C
Temperature ambient from	-30 °C
Temperature ambient to	100 °C
Material of body	Stainless steel 1.4305
Material of wetted parts	NBR, Stainless steel 1.4305
Material membrane	NBR

ADDITIONAL DATA



Supply voltage dc max	32 V DC
Supply voltage dc min	9.6 V DC
Pressure rise	≤ 1 bar/ms
Switching time	< 4 ms
Switching point adjustment range	3...100 % of adjustment range(full scale), set at factory
Weight	80 g

SAFETY & APPROVALS

IP class	IP67
Hysteresis	2...98% full scale, programmable at factory (maximum tolerance ±1.0% of adjustment range nominal pressure)
Shock resistance	500m / s ² ; 11 ms half sine wave; DIN EN 60068-2-27
Vibration resistance	20g: 4..2000 Hz sine wave, DIN EN 60068-2-6
EMC	EMC 2014/30/EU; EN 61000-6-2:2005; EN 61000-6-3:2007
Accuracy	±0.5 % of adjustment range (Full scale) at room temperature
Long term stability	±0.1 % of adjustment range (full scale) per year
Mechanical life expectancy	5,000,000 pulsations at rise rates to 1 bar/ms nominal pressure

Repeatability

±0.1 % of adjustment range (full scale)



DIN EN 175301-803-A

Pin	Assignment
1	U _{sup}
2	Gnd
3	U _{sup}
4	U _{sup}

IP67

• = 60 mm without cable outlet
 x = 77 mm with cable outlet

Order number: 013

M 12 - DIN EN 61076-2-101 A

Pin	Assignment
1	U _{sup}
2	nc
3	Gnd
4	U _{sup}

IP67

x = 54 mm

Order number: 002

ISO 15170-A1-4-1

Pin	Assignment
1	U _{sup}
2	nc
3	Gnd
4	U _{sup}

IP67, IP68/9K

x = 56 mm

Order number: 004

AMP Superseal 1.5"

Pin	Assignment
1	U _{sup}
2	Gnd
3	U _{sup}

IP67

x = 60 mm

Order number: 007

Deutsch DT04-3P

Pin	Assignment
1	A
2	Gnd
3	C

IP67, IP68/9K

x = 60 mm

Order number: 010

Thread code: 41

Thread code: 09



DIN EN 175301-803-A <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>U_{sup}</td></tr><tr><td>2</td><td>Gnd</td></tr><tr><td>3</td><td>U_{sup}</td></tr><tr><td>4</td><td>U_{sup}</td></tr></table> IP67 x = 60 mm without cable outlet x = 77 mm with cable outlet Order number: 013	Pin	Assignment	1	U _{sup}	2	Gnd	3	U _{sup}	4	U _{sup}	M 12 - DIN EN 61076-2-101 A <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>U_{sup}</td></tr><tr><td>2</td><td>nc</td></tr><tr><td>3</td><td>Gnd</td></tr><tr><td>4</td><td>U_{sup}</td></tr></table> IP67 x = 54 mm Order number: 002	Pin	Assignment	1	U _{sup}	2	nc	3	Gnd	4	U _{sup}	ISO 15170-A1-4-1 <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>U_{sup}</td></tr><tr><td>2</td><td>nc</td></tr><tr><td>3</td><td>Gnd</td></tr><tr><td>4</td><td>U_{sup}</td></tr></table> IP67, IP68/9K x = 56 mm Order number: 004	Pin	Assignment	1	U _{sup}	2	nc	3	Gnd	4	U _{sup}
Pin	Assignment																															
1	U _{sup}																															
2	Gnd																															
3	U _{sup}																															
4	U _{sup}																															
Pin	Assignment																															
1	U _{sup}																															
2	nc																															
3	Gnd																															
4	U _{sup}																															
Pin	Assignment																															
1	U _{sup}																															
2	nc																															
3	Gnd																															
4	U _{sup}																															
AMP Superseal 1.5" <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>U_{sup}</td></tr><tr><td>2</td><td>Gnd</td></tr><tr><td>3</td><td>U_{sup}</td></tr></table> IP67 x = 60 mm Order number: 007	Pin	Assignment	1	U _{sup}	2	Gnd	3	U _{sup}	Deutsch DT04-3P <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>A</td><td>U_{sup}</td></tr><tr><td>B</td><td>Gnd</td></tr><tr><td>C</td><td>U_{sup}</td></tr></table> IP67, IP68/9K x = 60 mm Order number: 010	Pin	Assignment	A	U _{sup}	B	Gnd	C	U _{sup}															
Pin	Assignment																															
1	U _{sup}																															
2	Gnd																															
3	U _{sup}																															
Pin	Assignment																															
A	U _{sup}																															
B	Gnd																															
C	U _{sup}																															
 Thread code: 41	 Thread code: 09																															