



SUCO 0510/0511 G1/4 ELECTRONIC PRESSURE SWITCH

Adjustable by user

0511161411007

NC, 0 - 16 Bar, G 1/4, NBR, AMP Superseal 1.5

- Single switch point
- Small & compact
- Ceramic sensor
- Stainless steel housing

PRODUCT DESCRIPTION

The SUCO performance series electronic pressure switch offers a small compact electronic switch without compromising on quality which comes adjustable by the user (hysteresis not adjustable) with overpressure protection (up to 2x), has a long service life and is also attractively priced especially at high volumes. Using a ceramic sensor in thick film technology for a good operating temperature range and accuracy, there are six standard pressure ranges starting from 0..2 bar all the way up to 0..100 bar and a hysteresis of 1%-98%, available in normally open or normally closed with a PNP output. The wetted parts are made of ceramic, stainless steel and either NBR, EPDM OR FKM ensuring excellent media compatibility, with six standard electrical connection options including Deutsch, DIN and M12 combined with two standard thread type options.

Customer specific solutions are also available on request.

Application examples

- Automotive
- Braking systems
- Medical
- Mobile hydraulics
- Off highway
- Off-shore
- Rail

TECHNICAL DATA

GENERAL DATA

| | |
|-----------------------|------------------------|
| Adjustment range max | 16 bar |
| Adjustment range min | 0 bar |
| Electrical connection | AMP Superseal |
| Process connection | G1/4 |
| Function | Normally Closed (SPST) |
| Output | PNP |
| Burst pressure | 60 bar |
| Pressure max | 40 bar |

TEMPERATURE & MATERIALS DATA

| | |
|---------------------------|-----------------------------|
| Temperature of media from | -30 °C |
| Temperature of media to | 100 °C |
| Temperature ambient from | -30 °C |
| Temperature ambient to | 100 °C |
| Material of body | Stainless steel 1.4305 |
| Material of wetted parts | NBR, Stainless steel 1.4305 |
| Material membrane | NBR |

ADDITIONAL DATA

| | |
|----------------------------------|---|
| Supply voltage dc max | 32 V DC |
| Supply voltage dc min | 9.6 V DC |
| Pressure rise | ≤ 1 bar/ms |
| Switching time | < 4 ms |
| Switching point adjustment range | 3...100 % of adjustment range(full scale), set at factory |

| | |
|--------|------|
| Weight | 80 g |
|--------|------|

SAFETY & APPROVALS

| | |
|----------------------------|--|
| IP class | IP67 |
| Hysteresis | 2...98% full scale, programmable at factory (maximum tolerance $\pm 1.0\%$ of adjustment range nominal pressure) |
| Shock resistance | 500m / s ² ; 11 ms half sine wave; DIN EN 60068-2-27 |
| Vibration resistance | 20g: 4..2000 Hz sine wave, DIN EN 60068-2-6 |
| EMC | EMC 2014/30/EU; EN 61000-6-2:2005; EN 61000-6-3:2007 |
| Accuracy | $\pm 0.5\%$ of adjustment range (Full scale) at room temperature |
| Long term stability | $\pm 0.1\%$ of adjustment range (full scale) per year |
| Mechanical life expectancy | 5,000,000 pulsations at rise rates to 1 bar/ms nominal pressure |
| Repeatability | $\pm 0.1\%$ of adjustment range (full scale) |



| |
|---------|
| no / nc |
| 1 (+) |
| 2 (GND) |
| 3 (OUT) |

| <p>DIN EN 175301-803-A</p> <table> <tr> <th>Pin</th> <th>Assignment</th> </tr> <tr> <td>1</td> <td>U_{ref}</td> </tr> <tr> <td>2</td> <td>Gnd</td> </tr> <tr> <td>3</td> <td>U_{sup}</td> </tr> <tr> <td>4</td> <td>U_{out}</td> </tr> </table> <p>IP67</p> <p>17 mm with cable seal</p> <p>Order number: 013</p> | Pin | Assignment | 1 | U _{ref} | 2 | Gnd | 3 | U _{sup} | 4 | U _{out} | <p>M 12 - DIN EN 61076-2-101 A</p> <table> <tr> <th>Pin</th> <th>Assignment</th> </tr> <tr> <td>1</td> <td>U_{ref}</td> </tr> <tr> <td>2</td> <td>nc</td> </tr> <tr> <td>3</td> <td>Gnd</td> </tr> <tr> <td>4</td> <td>U_{out}</td> </tr> </table> <p>IP67</p> <p>17 mm with cable seal</p> <p>Order number: 002</p> | Pin | Assignment | 1 | U _{ref} | 2 | nc | 3 | Gnd | 4 | U _{out} | <p>ISO 15170-A1-4-1</p> <table> <tr> <th>Pin</th> <th>Assignment</th> </tr> <tr> <td>1</td> <td>U_{ref}</td> </tr> <tr> <td>2</td> <td>nc</td> </tr> <tr> <td>3</td> <td>Gnd</td> </tr> <tr> <td>4</td> <td>U_{out}</td> </tr> </table> <p>IP67</p> <p>17 mm with cable seal</p> <p>Order number: 004</p> | Pin | Assignment | 1 | U _{ref} | 2 | nc | 3 | Gnd | 4 | U _{out} |
|---|------------------------|------------|---|------------------|---|-----|---|------------------|---|------------------|--|-----|------------|---|------------------|---|-----|---|------------------|---|------------------|---|-----|------------|---|------------------|---|----|---|-----|---|------------------|
| Pin | Assignment | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | U _{ref} | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | Gnd | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | U _{sup} | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | U _{out} | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Pin | Assignment | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | U _{ref} | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | nc | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | Gnd | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | U _{out} | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Pin | Assignment | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | U _{ref} | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | nc | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | Gnd | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | U _{out} | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>AMP Supersseal 1.5"</p> <table> <tr> <th>Pin</th> <th>Assignment</th> </tr> <tr> <td>1</td> <td>U_{ref}</td> </tr> <tr> <td>2</td> <td>Gnd</td> </tr> <tr> <td>3</td> <td>U_{sup}</td> </tr> <tr> <td>4</td> <td>U_{out}</td> </tr> </table> <p>IP67</p> <p>17 mm with cable seal</p> <p>Order number: 007</p> | Pin | Assignment | 1 | U _{ref} | 2 | Gnd | 3 | U _{sup} | 4 | U _{out} | <p>Deutsch DT98-3P</p> <table> <tr> <th>Pin</th> <th>Assignment</th> </tr> <tr> <td>A</td> <td>U_{ref}</td> </tr> <tr> <td>B</td> <td>Gnd</td> </tr> <tr> <td>C</td> <td>U_{out}</td> </tr> </table> <p>IP67</p> <p>17 mm with cable seal</p> <p>Order number: 010</p> | Pin | Assignment | A | U _{ref} | B | Gnd | C | U _{out} | | | | | | | | | | | | | |
| Pin | Assignment | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | U _{ref} | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | Gnd | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | U _{sup} | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | U _{out} | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Pin | Assignment | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| A | U _{ref} | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| B | Gnd | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| C | U _{out} | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Thread code: 41</p> | <p>Thread code: 00</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |



| |
|---------|
| no / nc |
| 1 (+) |
| 2 (GND) |
| 3 (OUT) |

| <p>DIN EN 175301-803-A</p> <table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>U_{ref}</td> </tr> <tr> <td>2</td> <td>Gnd</td> </tr> <tr> <td>3</td> <td>U_{ref}</td> </tr> <tr> <td>4</td> <td>U_{out}</td> </tr> </tbody> </table> <p>IP67</p> <p>17 mm with cable seal</p> <p>Order number: 013</p> | Pin | Assignment | 1 | U _{ref} | 2 | Gnd | 3 | U _{ref} | 4 | U _{out} | <p>M 12 - DIN EN 61076-2-101 A</p> <table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>U_{ref}</td> </tr> <tr> <td>2</td> <td>nc</td> </tr> <tr> <td>3</td> <td>Gnd</td> </tr> <tr> <td>4</td> <td>U_{out}</td> </tr> </tbody> </table> <p>IP67</p> <p>17 mm with cable seal</p> <p>Order number: 002</p> | Pin | Assignment | 1 | U _{ref} | 2 | nc | 3 | Gnd | 4 | U _{out} | <p>ISO 15170-A1-4-1</p> <table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>U_{ref}</td> </tr> <tr> <td>2</td> <td>nc</td> </tr> <tr> <td>3</td> <td>Gnd</td> </tr> <tr> <td>4</td> <td>U_{out}</td> </tr> </tbody> </table> <p>IP67</p> <p>17 mm with cable seal</p> <p>Order number: 004</p> | Pin | Assignment | 1 | U _{ref} | 2 | nc | 3 | Gnd | 4 | U _{out} |
|--|------------------------|------------|---|------------------|---|-----|---|------------------|---|------------------|---|-----|------------|---|------------------|---|-----|---|------------------|---|------------------|--|-----|------------|---|------------------|---|----|---|-----|---|------------------|
| Pin | Assignment | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | U _{ref} | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | Gnd | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | U _{ref} | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | U _{out} | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Pin | Assignment | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | U _{ref} | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | nc | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | Gnd | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | U _{out} | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Pin | Assignment | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | U _{ref} | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | nc | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | Gnd | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | U _{out} | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>AMP Supersseal 1.5"</p> <table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>U_{ref}</td> </tr> <tr> <td>2</td> <td>Gnd</td> </tr> <tr> <td>3</td> <td>U_{ref}</td> </tr> <tr> <td>4</td> <td>U_{out}</td> </tr> </tbody> </table> <p>IP67</p> <p>17 mm with cable seal</p> <p>Order number: 007</p> | Pin | Assignment | 1 | U _{ref} | 2 | Gnd | 3 | U _{ref} | 4 | U _{out} | <p>Deutsch DT98-3P</p> <table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>U_{ref}</td> </tr> <tr> <td>B</td> <td>Gnd</td> </tr> <tr> <td>C</td> <td>U_{out}</td> </tr> </tbody> </table> <p>IP67</p> <p>17 mm with cable seal</p> <p>Order number: 010</p> | Pin | Assignment | A | U _{ref} | B | Gnd | C | U _{out} | | | | | | | | | | | | | |
| Pin | Assignment | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | U _{ref} | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | Gnd | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | U _{ref} | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | U _{out} | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Pin | Assignment | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| A | U _{ref} | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| B | Gnd | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| C | U _{out} | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Thread code: 41</p> | <p>Thread code: 00</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

