

SUCO - 0705/0710/0720 PRESSURE SENSOR

High performance series

072025141B008
4-20mA, 0..25 bar, G1/4-E, Deutsch DT04-4P

- Measuring range up to 600 bar
- Silicon-on-sapphire sensor
- Outstanding overpressure protection
- Outstanding repeatability



PRODUCT DESCRIPTION

The SUCO 0705/0710/0720 high performance series pressure sensor is an advanced pressure monitoring solution with unrivalled attributes. Offering ten standard pressure ranges with options of six different electrical connectors a thread of G1/4 (eight available in total) and 0.5-4.5 V ratiometric, 0-10V or 4-20mA outputs. The 07 series uses silicon-on-sapphire technology in a titanium all welded design offering outstanding overpressure protection, media compatibility and the highest repeatability.

Common applications include mobile hydraulics, off-shore/marine, high pressure systems and more.

TECHNICAL DATA

Accuracy

±0.5% FS

| | |
|----------------------------------|---|
| Burst pressure | 200 bar |
| Connection | G1/4-E |
| Electrical connection | Deutsch DT04-4P |
| IP class | IP67, IP6K9K |
| Long term stability | ±0.1% FS p.a. |
| Material of body | Stainless steel 1.4305 |
| Material of wetted parts | Stainless steel 1.4305, Titanium |
| Overpressure protection | 100 bar |
| Pressure range max | 25 bar |
| Pressure range min | 0 bar |
| Pressure reference | Gauge |
| Pressure rise | 5 bar/ms |
| Repeatability | ±0.1% FS |
| Response time | 2 ms |
| Shock resistance | 500m / s ² ; 11 ms half sine wave; DIN EN 60068-2-27 |
| Signal type | 4-20 mA |
| Supply voltage dc max | 32 V DC |
| Supply voltage dc min | 10 V DC |
| Temperature ambient from | -40 °C |
| Temperature ambient to | 100 °C |
| Temperature error | ±0.01% FS/°C |
| Temperature of media from | -40 °C |
| Temperature of media to | 125 °C |
| Weight | 80 g |
| Vibration resistance | 20g: 4..2000 Hz sine wave, DIN EN 60068-2-6 |

