

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

## **ESI - GS4000 - INDUSTRIAL PRESSURE** SENSOR

GS4002B0700AB 0-10Vdc (4 wire), 0..700 bar, G1/4, M12

- · Suitable for the majority of industrial applications
- Reliable pressure measurement
- · Long service life
- All stainless steel construction



## PRODUCT DESCRIPTION

The ESI Technology GS4000 is a standard industrial pressure sensor designed to deal with the majority of general industrial applications.

The GS4000 offers a robust yet compact sensor that still offers good performance and is very reliable. The GS4000 starts from -1 - 0 bar up to 0 to 700 bar with a total of eight standard pressure ranges, four options of outputs including 4-20mA and 0-10V and also four different electrical connections including a DIN connector and M12.

Application examples

- Aerospace
- Power packs
- Mobile hydraulics

## **TECHNICAL DATA**

| Ambient temperature                           | -2085°C  |
|---|--|
| Approvals                                     | CE, IEC  |
| Electrical connection                         | M12  |
| EMC   | EN61000-6-4, EN61000-6-2                             |
| Linearity                                     | ≤±0.4% BSFL  |
|   |  |
| Material of wetted parts                      | Stainless steel 17-4, Stainless steel 303            |
| Material of wetted parts<br>Media temperature | Stainless steel 17-4, Stainless steel 303<br>-2085°C |
| -   |  |
| Media temperature                             | -2085°C  |

| Pressure range min  | 0 bar   |
|---------------------|---|
| Pressure reference  | Gauge   |
| Process connection  | G1/4  |
| Sensor technology   | Cereamic thick film or Bonded foil strain gauge |
|                     |   |
| Storage temperature | 540°C   |

