

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

## **ESI - GS4000 - INDUSTRIAL PRESSURE** SENSOR

GS4112B0010AB 0-10Vdc (3 wire), 0..10 bar, G1/4, M12

- · Suitable for the majority of industrial applications
- Reliable pressure measurement
- · Long service life
- All stainless steel construction



## PRODUCT DESCRIPTION

The ESI Technology GS4000 is a standard industrial pressure sensor designed to deal with the majority of general industrial applications.

The GS4000 offers a robust yet compact sensor that still offers good performance and is very reliable. The GS4000 starts from -1 - 0 bar up to 0 to 700 bar with a total of eight standard pressure ranges, four options of outputs including 4-20mA and 0-10V and also four different electrical connections including a DIN connector and M12.

Application examples

- Aerospace
- Power packs
- Mobile hydraulics

## **TECHNICAL DATA**

Ambient temperature	-2085°C
Approvals	CE, IEC
Electrical connection	M12
EMC	EN61000-6-4, EN61000-6-2
Linearity	≤±0.4% BSFL
Material of wetted parts	Aluminium oxide, Stainless steel 303, NBR
Material of wetted parts Media temperature	Aluminium oxide, Stainless steel 303, NBR -2085°C
-	
Media temperature	-2085°C

Pressure range min	0 bar
Pressure reference	Gauge or Absolute
Process connection	G1/4
Sensor technology	Cereamic thick film or Bonded foil strain gauge
Storage temperature	540°C
Supply voltage	13-30 V DC

