

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

ESI - GS4000 - INDUSTRIAL PRESSURE SENSOR

GS4112C0.05AB 0-10Vdc (3 wire), 0..0,5 bar, G1/4, 1M cable IP67

- · Suitable for the majority of industrial applications
- Reliable pressure measurement
- · Long service life
- All stainless steel construction



PRODUCT DESCRIPTION

The ESI Technology GS4000 is a standard industrial pressure sensor designed to deal with the majority of general industrial applications.

The GS4000 offers a robust yet compact sensor that still offers good performance and is very reliable. The GS4000 starts from -1 - 0 bar up to 0 to 700 bar with a total of eight standard pressure ranges, four options of outputs including 4-20mA and 0-10V and also four different electrical connections including a DIN connector and M12.

Application examples

- Aerospace
- Power packs
- Mobile hydraulics

TECHNICAL DATA

| Ambient temperature | -2085°C |
|--------------------------|---|
| Approvals | CE, IEC |
| Electrical connection | 1M Cable outlet screened (IP67) |
| EMC | EN61000-6-4, EN61000-6-2 |
| Linearity | ≤±0.4% BSFL |
| Material of wetted parts | Aluminium oxide, Stainless steel 303, NBR |
| Media temperature | -2085°C |
| Output | 0-10Vdc |
| Overpressure protection | 0.8 bar |

| Pressure range max | 0.5 bar |
|---------------------|---|
| Pressure range min | 0 bar |
| Pressure reference | Gauge or Absolute |
| Process connection | G1/4 |
| Sensor technology | Cereamic thick film or Bonded foil strain gauge |
| Storage temperature | 540°C |
| Supply voltage | 13-30 V DC |

