



## ESI - GS4200 UP TO 25 BAR PRESSURE

### General Pressure Sensor

GS4203AV001AB

0-10V (4 wire), -1..0 bar, G1/4, 1M cable

- Silicon-on-sapphire sensor technology
- Pressure ranges up to 25 bar
- Unblemished track record of reliability
- Titanium wetted parts



### PRODUCT DESCRIPTION

The ESI Technology GS4200 pressure sensor is designed to meet the operational requirements of demanding pressure measurement applications where good quality, fast delivery and low cost are of the highest priority.

The unique Silicon-on-Sapphire (SOS) sensor technology provides outstanding performance and gives excellent stability over a wide temperature range. The all titanium alloy wetted parts offer unbeatable corrosion resistance making it suitable for a wide range of applications. The GS4200 starts from -1 to 0 bar up to 0 to 1500 bar with a total of fourteen standard pressure ranges, four options of outputs including 4-20mA and 0-10V and also four different electrical connections including a DIN connector and M12.

This transmitter is truly unique with its versatility matched with high accuracy, impressive over pressure safety, reliability and low temperature error,

#### Application examples

- Aerospace
- Automotive
- Heavy duty
- Mobile hydraulics
- Off-shore (Sea/salt water)
- Process

### TECHNICAL DATA

|                          |                          |
|--------------------------|--------------------------|
| Ambient temperature      | -40..85°C                |
| Approvals                | CE, DNV, IEC             |
| Electrical connection    | 1M Cable outlet screened |
| EMC                      | EN61000-6-3, EN61000-6-2 |
| Linearity                | ≤±0.25% BFSL             |
| Material of wetted parts | Titanium alloy           |
| Media temperature        | -50..125°C               |

|                                |                     |
|--------------------------------|---------------------|
| <b>Output</b>                  | 0-10V               |
| <b>Overpressure protection</b> | 2 bar               |
| <b>Pressure range max</b>      | 0 bar               |
| <b>Pressure range min</b>      | -1 bar              |
| <b>Pressure reference</b>      | Gauge               |
| <b>Process connection</b>      | G1/4                |
| <b>Sensor technology</b>       | Silicon-on-Sapphire |
| <b>Storage temperature</b>     | 5..40°C             |
| <b>Supply voltage</b>          | 13-30 V DC          |

