



## ESI - PR3202 - DIFFERENTIAL PRESSURE SENSOR

PR3202EX0001AW  
4-20mA, 0..1 bar, 4.8mm tube stem x2, PG7 cable gland, Ex

- Piezoresistive Silicon sensor technology
- Wide range of pressure ranges from ultra-low to 200 barDP
- wet/wet OR dry/dry OPERATION
- Durable designs for industrial and commercial installations



### PRODUCT DESCRIPTION

The PR3202 air differential pressure transmitter gives you a precise solution for low pressure sensing, and is fully temperature compensated for unrivalled stability at very low pressures. Housed in a RFI protected shielded mountable box for EMC security, these transmitters combine exact measurement for control at extremely low pressure, with the robustness and adaptability for industrial and commercial installations. An optional heavy-duty aluminium die-cast housing is available for the harshest environments.

There are optional ATEX and IECEx approved versions of the PR3202 available for explosion protection for flammable gases (zone0), dusts (zone 20) and mining areas (group I M1).

### TECHNICAL DATA

|                          |   |
|--------------------------|---|
| Ambient temperature      | -20..70°C   |
| Approvals                | CE, IEC   |
| ATEX approved            | Yes   |
| Electrical connection    | PG7 Cable gland   |
| EMC                      | EN61000-6-2, EN61000-6-4  |
| EX approvals             | Ex II 1 D Ex ia IIIC T135 °C Da, Ex II 1 G Ex ia IIC T4 Ga, Ex I M 1 Ex ia I Ma |
| Linearity                | ≤±0.3% BSFL   |
| Material of wetted parts | Nickel-plated brass   |
| Media temperature        | -20..70°C   |
| Output                   | 4-20 mA   |
| Overpressure protection  | 1.2 bar   |
| Pressure range max       | 1 bar   |

|                            |                        |
|----------------------------|------------------------|
| <b>Pressure range min</b>  | 0 bar                  |
| <b>Pressure reference</b>  | Differential           |
| <b>Process connection</b>  | 4.8mm tube connection  |
| <b>Sensor technology</b>   | Piezoresistive Silicon |
| <b>Storage temperature</b> | 5..40°C                |
| <b>Supply voltage</b>      | 10-36 V DC             |