**OEM Automatic Ltd**
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# ESI - PR3100 - INDUSTRIAL PRESSURE SENSOR

PR3101A0100AC
2mV/V, 0..100 bar, G1/2, 1M cable

- Suitable for the majority of industrial applications
- Reliable pressure measurement
- Long service life
- All stainless steel construction

### PRODUCT DESCRIPTION

The PR3100 is constructed from stainless steel which incorporates thick film, ceramic and bonded strain gauge technology. This offers excellent stability and accuracy over a long service life. On request this is also available in corrosion resistant materials. The available pressure range options are from 0-1Bar to 0-600Bar.

There are optional ATEX and IECEx approved versions of the PR3100 available for Explosion protection for flammable gases (zone0), dusts (zone 20) and mining areas (group I M1).

## TECHNICAL DATA

| | |
|---|---|
| **Ambient temperature** | -20..85°C |
| **Electrical connection** | 1M Cable outlet screened |
| **EMC** | EN61000-6-4, EN61000-6-2 |
| **Linearity** | ≤±0.3% BSFL |
| **Material of wetted parts** | Stainless steel 316, Stainless steel 17-4 |
| **Media temperature** | -20..85°C |
| **Output** | 2mV/V |
| **Overpressure protection** | 200 bar |
| **Pressure range max** | 100 bar |
| **Pressure range min** | 0 bar |
| **Pressure reference** | Gauge or Absolute |
| **Process connection** | G1/2 |

| | |
|---|---|
| **Sensor technology** | Thick film or Bonded foil strain gauge |
| **Storage temperature** | 5..40°C |
| **Supply voltage** | 10 V DC (5-15 V) |